

研發、職訓、教學用實驗室型設備

- 印刷電路板少量多樣製作整廠設備及耗材
- 晶片、玻璃、銅板、鋁板、鎳板、鋼板...
之乾膜壓合、曝光、顯影、蝕刻裁切設備

Conveyorised

Spray Processing Equipment

New from Mega is a range of Conveyorised Processing Modules consisting of high quality double and single sided units for developing, stripping and etching various materials to 500mm wide. These machines offer the ultimate in efficiency for either PCB or metal etch sign applications. The conveyor takes the material through the process chamber and a rinse chamber so completely clean panels exit the machine. 500mm modules should be ordered with a stand but the 300mm modules can be bench mounted.

NEW

Features include:



- 500mm or 300mm conveyor widths
- Modular construction
- Variable Spray Pressure
- Full safety features
- Digital temperature control
- Low maintenance
- Double filtration of the chemistry
- Low voltage control circuits.

Accessories available for the processor include a stand, link inspection modules, catch trays and cooling systems.



Illustrated model DL500DS with stand

Description	Chemical spray processor including mains water rinse
Process chamber	460mm all models
Mains water rinse chamber	380mm for CP500, 295mm for CP300
Spray bars - top	4 process chamber, 1 rinse chamber
Spray bars - bottom	4 process chamber, 1 rinse chamber
Nozzle type	Poly v-jet
Nozzles per tube	5 + 6 for CP500, 3 + 4 for CP300
Pressure indication	Optional extra
Pressure control	Adjustable over full operating range
Re-circulating pump	CP500 - 0.75kW magnetic drive centrifugal pump, 0.5kW for CP300
Conveyor drive	Worm and wheel
Speed range	Variable speed d.c. shunt wound motor
Speed direction	0-2 metres/minute
Temperature range	Ambient to 50°C ± 1°C
Controller	Digital (standard)
Cooling	Factory build optional extra
Sump capacity max.	CP500 - 90 litres. CP300 - 30 litres
Sump capacity min.	CP500 - 50 litres. CP300 - 25 litres
Liquid low level and shut down	Warning lamp
Construction materials	P.V.C. Titanium, Hyperlon, PE1000, Vinylester, H.M.P., P.V.D.F.
Lids	Glass inner and outer with P.V.C. seals
Covers	P.V.C.
Safety switches	Reed magnetic on outer lids and rear cover
Voltage	220/240v 50Hz (13A plug)
Dimensions	Height CP500 - 810mm. CP300 - 655mm Width CP500 - 1000mm. CP300 - 795mm Length CP500 - 1120mm. CP300 - 1050mm
Mounting Frame	Polypropylene box section (Optional extra)
Heater	2Kw Hair Pin Titanium



吉爾泰國際有限公司
GIGATECH INTERNATIONAL CO., LTD

110 台北市忠孝東路五段482號9樓之7
TEL: 886-2-27279958 FAX: 886-2-27279658
E-mail: giga1688@ms78.hinet.net